

CCT-3 COLORS  
3000K 4000K 6000K



## **DOWNLIGHT LED TEMPERATURA SELECCIONABLE 20W OSRAM UGR17 17CM IP54 2400LM**

**23,20€ IVA incluido**

Downlight circular fabricado en aluminio y con acabado en blanco. Con **20W de potencia**, su **temperatura de color es CCT**, es decir, podrás elegir entre 3000K, 4000K y 6000K. Su **chip OSRAM** le proporciona una **alta eficiencia lumínica y energética**. Además, con su **UGR17 evitarás los deslumbramientos** y su alto índice de reproducción cromática garantiza una emisión de los colores de la luz de forma natural. Por otro lado, su instalación es muy sencilla gracias a su diseño simple y delgado. Es perfecta para tiendas, restaurantes, museos, centros comerciales, etc.

---

**SKU:** 90806

**Category:** [Focos LED empotrables](#)

**Tags:** [Downlight LED regulables](#), [Focos LED empotrables extraplanos](#)

## **DATOS TÉCNICOS**

|                               |               |
|-------------------------------|---------------|
| <b>Peso</b>                   | 0.480000      |
| <b>Vatios</b>                 | 20W           |
| <b>Acabado</b>                | Blanco        |
| <b>Alimentación</b>           | 85-265V       |
| <b>Temperatura de color</b>   | CCT           |
| <b>IRC</b>                    | 85            |
| <b>Material</b>               | Aluminio + PC |
| <b>Eficiencia Energética</b>  | A+            |
| <b>Lúmenes</b>                | 2400          |
| <b>Ángulo de Apertura (º)</b> | 120º          |
| <b>Eficacia luminosa</b>      | 120lm/w       |
| <b>Certificados</b>           | CE - ROHS     |
| <b>Protección IP</b>          | IP54          |
| <b>Tamaño</b>                 | 17 x 3,5cm    |
| <b>Frecuencia de Trabajo</b>  | 50/60Hz       |
| <b>Temperatura Soportada</b>  | -20°C ~ +55°C |
| <b>Ciclos de Encendidos</b>   | 100000        |
| <b>Tiempo de Arranque</b>     | 0,2s          |
| <b>Tamaño de corte</b>        | 16,3cm        |
| <b>UGR</b>                    | 17            |
| <b>Garantía</b>               | 3 años        |
| <b>Forma</b>                  | Circular      |

## GALERÍA DE IMÁGENES



**OSRAM**  
LEDs Included

**3 COLORS INSIDE:**

3000 4000 6000

**AROSA**  
LED Downlight | UGR17

switch to  
**down  
light!**

**OSRAM**  
LEDs Included



The advertisement shows three white circular LED downlights at the top. Below them, three different light colors (3000K, 4000K, 6000K) are demonstrated in a room setting. The AROSA LED Downlight is shown in a close-up view with technical icons. At the bottom, a child is looking through a telescope, symbolizing the 'switch to down light!' slogan.

[www.osram-os.com](http://www.osram-os.com)


### GWM JTLRSA.EM

#### DURIS® E 2835

The DURIS® E 2835 combines good efficacy and a wide beam angle into a compact format (2.8 mm x 3.5 mm). This is key to homogeneous illumination applications where the DURIS® E 2835 never fails to impress with its performance on system level.



Complete with 1000mA driver.





Select color:  
Daylight - Cool white - Warm white

3000K 4000K 6000K

A color spectrum bar is shown below the text, ranging from 3000K (yellow) to 6000K (blue).

Dimensions



**TODAVÍA NO HAY VALORACIONES**